



| | | |
|---|----------------------------------------|-----------|
| A | Total length | 4,590 mm |
| B | Total width | 2,095 mm |
| C | Height to top of steering wheel | 2,160 mm |
| D | Wheelbase | 2,450 mm |
| E | Height to front lip of Skip (untipped) | 1,760 mm |
| F | Ground clearance | 380 mm |
| G | Height to top of ROPS | 2,910 mm |
| H | Height to front lip of bucket | 1,100 mm |
| | Turning radius outside of bucket | 5,600 mm |
| | Steering angle | +/- 30° |
| | Oscillation | +/- 10.5° |
| | Tipping type | Swing |

| | |
|------------------------------|----------------------------------|
| Payload | 6,000 kg |
| Unladen weight | 4,270 kg |
| Skip capacity - Water | 1,850 ltr |
| - Struck | 2,750 ltr |
| - Heaped | 3,520 ltr |
| Engine | Perkins 1104D-44T |
| - Net power - kW (hp) | 62.5 (84hp) at 2200rpm |
| - Capacity | 4.4 litres (4400 cc) |
| - Maximum torque | 353 Nm at 1400rpm |
| Tyre size | 405/70-20-14PR |
| Drive | 4/4 Powershuttle - permanent 4WD |
| Max travel speed - mph (kph) | 16.8 (27.0) |
| Gradeability | 25% |
| Fuel tank capacity | 67 Litres |
| Hydraulic tank capacity | 50 Litres |